

WL290

High capacity refreshing water on demand

The WL290 delivers superb quality water and satisfies the higher volume needs for cold and hot water in the most demanding environments. It is specifically designed for use where reverse osmosis is preferred, or for low pressure installations. The WL290 also has the added quality assurance of in-tank ultraviolet light sanitization. This high performance model guarantees quality water all day long, and provides 4x cold water capacity compared to the WL270 model.



Advanced Technology

The WL290 has the following core technologies:



1. High Performance Filtration: This model can be configured with four stage reverse osmosis filtration or multistage carbon filtration depending on water conditions. These processes remove water contaminants and chlorine to improve water taste and odor.



2. In-tank UV Sanitization: The recirculating cold water system passes water by the UV multiple times every hour to maintain the microbiological purity of the water.



3. BioCote® Anti-Microbial Protection: The WL290 water treatment system is BioCote® protected to provide an effective barrier against microbes like bacteria and mold, which may cause odors or staining.

* For more information visit www.biocote.com/home-us.

Good for the Earth

Waterlogic coolers have been shown to reduce carbon footprint by up to 72% compared to bottled water coolers*. Bottleless water coolers reduce plastic bottle contribution to landfills.

* Waterlogic 2014
www.waterlogic.com/benefits/simply-green/carbon-reduction-label

WL 290 Features

- Large chilled recirculating reservoir for high capacity cold water production
- Improved design allows for 4x more cold water capacity
- The recirculating cold water system passes water by the UV multiple times every hour to maintain the microbiological purity of the water
- GAC filter inside the cold reservoir to provide ongoing protection from taste and odors
- Choice of Reverse Osmosis or Carbon Filtration to fit local water conditions.
- Ultraviolet technology reduces bacterial growth
- Large water storage capacity for a constant supply of cold water on demand
- Gravity-fed storage tank providing additional stored water for the Reverse Osmosis system also ideal for low pressure installations



The Boring Bits

Water Options	Technical Features	
	Type available	Tower
	Dimensions	15.5" (W) x 46" (H) x 14.5" (D)
	Dispense area height	9.0"
	Weight	Tower: 62 LBS
	Recommended filtration	Reverse Osmosis, Sediment, GAC, CBC with lead and cyst removal
Symbols	Additional Features	
Cold water Hot water	Leak detection Thermistor controls Hybrid Stainless Steel cold tank with cooling coils for efficient cooling Programmable Temperature Settings Optional Sleep Mode Optional Filter Timer Programmable Hot and Cold temperature Internal GAC filter Built-in diagnostics	
	Capacity	Cold Tank: 4 liter hybrid tank with 11.2 liters chilled reservoir Hot Tank: 1.5 liters
	Compressor	110v / 60Hz compressor
	Factory set	Cold: 41° F Hot: 185° F

Tested and Certified



Waterlogic International Limited and WLI Trading Limited reserves the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd is licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Speak to a Water Expert

Waterlogic USA

11710 Stonegate Circle
Omaha, NE 68164

Tel: +1 402 905 2001
800 288 1891

customerservice@waterlogicausa.com
www.waterlogicausa.com

For a full list of our offices, visit www.waterlogic.com